

SINGLE-STAGE CENTRIFUGAL PUMP WITH MAGNETIC DRIVE ACC. ASME



SERIES SLM AV

ACCORDING ASME B73.3

MAX. FLOW RATE:

200 M³/H

881 USGPM

TEMPERATURE RANGE:

-200 °C to +450 °C

-328 °F to +842 °F

MAX. DELIVERY HEAD:

155 M L.C.

509 FT

MAX. PRESSURE RATING:

PN 400

5,802 PSI

DESIGN

- ▶ Horizontal centrifugal pump, process design
- ▶ Hydraulic performance and dimensions according to ASME B73.3
- ▶ Permanent & synchronous magnetic drive
 - Maintenance-free
 - Separation of liquid chamber and atmosphere by means of containment shell
- ▶ Pressurized partial flush flow (cooling of eddy current losses / lubrication of journal bearings)
- ▶ Materials: steel, stainless steel, duplex steel, nickel-based materials, titanium
- ▶ Bearing bracket with anti-friction bearings, oil-lubricated or greased-for-life
- ▶ Product-lubricated journal bearings; made of silicon carbide (SSiC) or customized materials
- ▶ Rub zones as per standard for increased safety
- ▶ Close-coupled design (SLM AVB)

PUMPING OF

- ▶ Acids
- ▶ Aggressive, explosive, toxic, hot and malodorous liquids
- ▶ Coolants
- ▶ Dyes and paints
- ▶ Heat transfer liquids
- ▶ Hot water
- ▶ Hydrocarbons
- ▶ Liquid gases
- ▶ Liquids containing solids
- ▶ Lyes
- ▶ Molten sulfur
- ▶ Refrigerants
- ▶ Salt solutions
- ▶ Sea water
- ▶ Solvents
- ▶ Valuable liquids
- ▶ And many more

MANY
OPTIONS
AVAILABLE

